

MATERIAL SAFETY DATA SHEET
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY (As Used on Label and List)

BRADY LEMON OIL FURNITURE POLISH

SECTION I

Distributor's Name	Emergency Telephone Number
BRADY INDUSTRIES, INC.	(800) 424-9300
Address (Number, Street, City, State & ZIP Code)	Telephone Number for Information
4175 SOUTH ARVILLE	(702) 876-3990
LAS VEGAS, NEVADA 89103	Date Prepared
	7/10/02 Supercedes 3/24/01
	Signature of Preparer (optional)

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Recommended Other Limits	% (optional)
---	----------	-----------	--------------------------	--------------

TECHNICAL OIL	CAS #8042-47-5			>50%
OSHA PEL/ACGIH TLV, NO LIMIT				

HAZARD RATING:	HEALTH	=	1
4-EXTREME	FIRE	=	1
3-HIGH	REACTIVITY	=	0
2-MODERATE	SPECIFIC HAZARDS	=	N/A
1-SLIGHT			
0-INSIGNIFICANT			

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	Specific Gravity (H20 = 1)
IBP 570°F	0.843 @60/60 F
Vapor Pressure (mm Hg)	Melting Point
N/A	N/A
Vapor Density	Evaporation Rate (Butyl Acetate = 1)
N/A	N/A
Solubility in Water	pH
SOLUBLE IN HYDROCARBONS	NEUTRAL

Appearance and Odor
LIGHT YELLOW LIQUID WITH A LEMON FRAGRANCE

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Flammable Limits	LEL	UEL
335°F	AIR % BY VOLUME	NO DATA	NO DATA

Extinguishing Media
USE DRY CHEMICAL, FOAM OR CARBON DIOXIDE

Special Fire Fighting Procedures
WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

Unusual Fire and Explosion Hazards
DENSE SMOKE MAY BE GENERATED WHILE BURNING. CARBON MONOXIDE, CARBON DIOXIDE, AND OTHER OXIDES MAY BE GENERATED AS PRODUCTS OF COMBUSTION.

(Reproduce locally)

OSHA 174, Sept. 1985

SECTION V - REACTIVITY DATA

Stability	Unstable	Conditions to Avoid:	NONE
Stable	XXX		

Incompatibility (Materials to Avoid)
MAY REACT WITH STRONG OXIDIZING AGENTS.

Hazardous Decomposition or Byproducts

NONE

Hazardous May Occur Conditions to Avoid: NONE

Polymerization Will Not Occur XXX

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry: Inhalation? Skin? Ingestion?
YES NO NO

Health Hazards (Acute and Chronic)

EXPOSURE TO A LARGE SINGLE DOES, OR REPEATED SMALL DOSES OF MINERAL OIL BY INHALATION, ASPIRATION OR INGESTION LEADING TO ASPIRATION CAN LEAD TO LIPID PNEUMONIA OR LIPID GRANULOMA.

Emergency and First Aid Procedures

EYES: IMMEDIATELY FLUSH EYES WITH LARGE AMOUNTS OF WATER AND CONTINUE FLUSHING UNTIL IRRITATION SUBSIDES. IF MATERIAL IS HOT, TREAT FOR THERMAL BURNS AND TAKE VICTIM TO HOSPITAL IMMEDIATELY.

SKIN: REMOVE CONTAMINATED CLOTHING. IF MATERIAL IS HOT, SUBMERGE INJURED AREA IN COLD WATER. IF VICTIM IS SEVERELY BURNED, REMOVE TO A HOSPITAL IMMEDIATELY.

INHALATION: THIS MATERIAL HAS A LOW VAPOR PRESSURE AND IS NOT EXPECTED TO PRESENT AN INHALATION EXPOSURE AT AMBIENT CONDITIONS.

INGESTION: MAY ACT AS A LAXATIVE. DO NOT INDUCE VOMITING DUE TO ASPIRATION HAZARD. IF VOMITING OCCURS, LOWER HEAD BELOW KNEES TO AVOID ASPIRATION. SEEK IMMEDIATE MEDICAL ATTENTION.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled

NOTIFY APPROPRIATE AUTHORITIES OF SPILL. CONTAIN SPILL IMMEDIATELY. DO NOT ALLOW SPILL TO ENTER SEWERS OR WATERCOURSES. REMOVE ALL SOURCES OF IGNITION. ABSORB WITH APPROPRIATE INERT MATERIAL SUCH AS SAND, CLAY, ETC. LARGE SPILLS MAY BE PICKED UP USING VACUUM PUMPS, SHOVELS, BUCKETS, OR OTHER MEANS AND PLACED IN DRUMS OR OTHER SUITABLE CONTAINERS.

Waste Disposal Method

COMPLY WITH STATE, FEDERAL AND LOCAL REGULATIONS.

Precautions to Be Taken in Handling and Storing

DO NOT TRANSFER TO UNMARKED CONTAINERS. STORE IN CLOSED CONTAINERS AWAY FROM HEAT, SPARKS, OPEN FLAME, OR OXIDIZING MATERIALS. THIS PRODUCT IS NOT CLASSIFIED AS HAZARDOUS UNDER D.O.T. REGULATIONS. FIRE EXTINGUISHERS SHOULD BE KEPT READILY AVAILABLE. SEE NFPA 30 AND OSHA 1910.106---FLAMMABLE AND COMBUSTIBLE LIQUIDS.

Other Precautions

THIS PRODUCT IS NOT KNOWN TO CONTAIN ANY SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS AT OR GREATER THAN 1.0% (0.1% FOR CARCINOGENS). THIS PRODUCT IS ON THE TOXIC SUBSTANCES CONTROL ACT (TSCA) INVENTORY.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type)

NONE REQUIRED UNDER CONDITIONS OR NORMAL USE.

Ventilation	Local Exhaust	Special
	IF HEATED	N/A
	Mechanical (General)	Other
	N/A	N/A

Protective Gloves Eye Protection

Other Protective Clothing or Equipment

Work/Hygienic Practices: USE CARE AND COMMON SENSE